



Plate Finish™

Product Description

VHT® Plate Finish™ is a unique quick drying formulation specifically created for application on metal, glass, wood or sealed plaster surfaces. This non-tarnishing epoxy finish has outstanding brilliance and corrosion resistance. It is easy to use and dries in minutes. Excellent for touch-up, refinishing, and decorative applications.

Product Characteristics

Color: Chrome Plus

Finish: High Gloss

Properties

Product Weight: 6.24 lbs/gal

Flash Point: Propellant < 0° F

Coating System

VHT provides a multi-high performance coating system for the ultimate in protection and quality. This system includes surface preparation and Plate Finish.

Prep SP445 Prep Spray

Coat SP5251 Plate Finish

Uses

Instrumentation, Picture Frames, Tail Light Reflectors, Pottery Lamps, and Outdoor Lighting

Surfaces:

- Metal, Glass, Wood, or Sealed Plaster Surfaces.

Application

Caution: For maximum product performance read entire label and directions prior to paint application

Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. Use grease and wax remover to clean surface.

Lightly sand surface with 320-grit sandpaper or Red Scotch Brite pad.

Wipe surface down again with grease and wax remover.

Mask-off surrounding areas to protect from overspray. Use at temperatures between 60° F (16° C) and 95° F and (35° C) and when humidity is less than 60%.

Shake can vigorously for 1 full minute after mixing ball moves freely. Shake can for 10 seconds after each minute of use. If bare metal is exposed, add VHT Prime Coat primer or equivalent first. To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. Apply 2 light coats, followed by one medium wet coat. Apply all coats within 1 hour, allowing 10 minutes between each coat. For additional coats after one hour, wait 7 days for paint to cure. Dries to touch in 20 minutes, and can be handled in 3 hours. Covers about 12-14 square feet.

The EZ TOUCH® Nozzle requires 50% less finger fatigue than a standard nozzle. It allows for greater coverage and less overspray.

No curing required.

Packaging

Fill Weight: 11.25 oz

Per Case: 6 cans

Case Weight: 5.82 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans